#	PART	QTY.	Tighton to F7 ft lb (77 Nm)	
-	Ramsey 251128/295137 Channel	1	Tighten to 57 ft-lb (77 Nm)	
2	Ramsey 251152 Hawse Fairlead	1		
	Ramsey REP-6000 Winch Assembly	1	$\sqrt{}$)
	Driver Side Tow Eye	1		/
	Passenger Side Tow Eye	1		
6	5/16" Front Channel Spacer	2		
7	1/2" Rear Channel Spacer	2		
8	1/2" ID (7/16" USS) Grade 5 Washer	4		
9	1/2"-13 x 2" Grade 5 Hex Bolt	4	(5)	
10	3/8" ID (5/16" USS) Grade 5 Washer	4		
11	3/8" Grade 5 Split Lock Washer	6		
12	3/8"-16 Grade 5 Hex Nut	6		_
	3/8"-16 x 1-1/8" Grade 5 Hex Bolt	2		
14	3/8"-16 x 1-1/4" Grade 5 Hex Bolt	4		
No	tes:		(10)	
1.	Ramsey 251128 production as of 2	2021	(13)	
	does not match the 1992 design	1/	4	
	shown. Substitute HFT 90476 or 624 for a more visually accurate style.	46		
2.	For greater strength, substitute #8	and		
	#9 for Grade 8 and tighten to 80 f			
3.	For greater strength, substitute on)
	winch feet only #10, #11, #12, and			
4.	#14 for Grade 8 and tighten to 33 For superior corrosion resistance,	II-ID.		
٦.	substitute on hawse fairlead only	#11,		
	#12 and #13 for stainless steel.			
		4		
	(12)			
				_
	(2)		/ (11) (7)	
				_
		Tic	ghten to 23 ft-lb (31 Nm) $/$ (14)	
K	TOR.COM	<u>···s</u>		/